



# MINERAL RENDER EWI-060

# **SAFETY SHEET**

According to 1907/2006/EC, Article 31

Revision: 13.04.2023

Printing date 00.00.0000

Version number: RO/ 4



# MINERAL RENDER EW-060 SAFETY SHEET

According to 1907/2006/EC, Article 31

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

# **1.1 PRODUCT IDENTIFIER**

Product form: Product name: Product code: Type of product: Powder EWI-060 Mineral Render EWI-060 Render

## 1.2 RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

Use of substance / mixture: Sector of Use: This product is used for securing insulation boards to external walls.

# **SECTION 2: HAZARDS IDENTIFICATION**

# 2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

Classification under CLP:

STOT SE 3: H335 Eye Dam. 1: H318 Skin Irrit. 2: H315 Skin Sens. 1A: H317

#### Most important adverse effects:

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation.

## **2.2 LABEL ELEMENTS**

Hazard statements: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.H318: Causes serious eye damage.H335: May cause respiratory irritation.

Hazard pictograms: GHS05: Corrosion GHS07: Exclamation mark



Signal words: Danger

#### Precautionary statements:

P102: Keep out of reach of children.
P261: Avoid breathing dust.
P271: Use only outdoors or in a well-ventilated area.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352: IF ON SKIN: Wash with plenty of water.
P332+P313: If skin irritation occurs. Seek medical advice/attention.
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P315: Seek immediate medical advice/attention.
P362+P364: Take off contaminated clothing and wash it before reuse.
P501: Dispose of contents/container to appropriate waste collection point.

# **2.3 OTHER HAZARDS**

This product is not identified as a PBT/vPvB substance.

# **SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS**

# **3.1 SUBSTANCE**

#### This product is a mixture.

# **3.2 MIXTURE**

Reg.nr.: -

Description: Mixture of inorganic binders, fillers and nonhazardous additions

#### Dangerous components:

<u></u>				
CAS: 1305-62-0 EINECS: 215-137-3 Reg.nr.: 01-2119475151-45	Calcium dihydroxide Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	10-25%		
CAS: 65997-15-1 EINECS: 266-043-4 Reg.nr.: 02-2119682167-31	Portland cement clinker Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	2.5-10%		
Other components:				
CAS: 1317-65-3 EINECS: 215-279-6	Limestone (Calcium carbonate)	50-100%		

Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: FIRST AID MEASURES**

# **4.1 DESCRIPTION OF FIRST AID MEASURES**

**Skin contact:** Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.

**Eye contact:** Rinse the eye with running water for 15 minutes. Do not rub eyes, as additional cornea damage is possible by mechanical stress. Contact a specialist of occupational medicine or an eye specialist.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Get medical attention if any discomfort continues.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If symptoms develop, seek medical attention.

# 4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Skin contact: There may be irritation and redness at the site of contact.

**Eye contact:** There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

# 4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

Immediate / special treatment: Eye bathing equipment should be available on the premises.

# SECTION 5: FIRE-FIGHTING MEASURES

### 5.1 EXTINGUISHING MEDIA

**Extinguishing media:** The mixture is fire resistant in both delivery condition and mixed condition. In the event of a fire, the mixture will not need extinguishing.

## 5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

**Exposure hazards:** This product is neither explosive nor flammable, and non-oxidizing with other materials. Dust formations react alkaline with water and can cause a fire risk.

**5.3 ADVICE FOR FIRE-FIGHTERS** 

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

# **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

**Personal precautions:** Avoid formation of dust. Avoid inhalation, eye and skin contact. If appropriate, reference must be made to exposure controls and personal protection (see section 8).

**6.2 ENVIRONMENTAL PRECAUTIONS** 

Environmental precautions: Do not discharge into drains or rivers.

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4 REFERENCE TO OTHER SECTIONS

Reference to other sections: Refer to section 8 of SDS.

# **SECTION 7: HANDLING AND STORAGE**

# 7.1 PRECAUTIONS FOR SAFE HANDLING

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of dust in the air.

## 7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

**Storage conditions:** Store in a cool, well-ventilated area. Keep the container tightly closed. **Suitable packaging:** Must only be kept in original packaging.

## 7.3 SPECIFIC END USE(S)

Specific end use(s): No data available.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

# 8.1 CONTROL PARAMETERS

DNELs					
1305-62-0 Calcium dihydroxide					
Inhalation	DNEL (8h) DNEL (15min.) 4 mg/m <sup>3</sup> (Workers)	1 mg/m <sup>3</sup> (Workers) 4 mg/m <sup>3</sup> (Workers)			
Additional Occupational Exposure Limit Values for possible hazards					
Components with general dust limit					
MAK D (TRGS 900) (PL)	Short-term value: 2.5 A 20 E mg/m <sup>3</sup> Long-term value: 1.25 A 10 E mg/m <sup>3</sup> A - IFA 6068 (2003) E - IFA 7284 (2003) Germany				

A - Alveoles passing particles E - Respirable particles (DIN EN 481)

# **8.2 EXPOSURE CONTROLS**

**Engineering measures:** Ensure there is sufficient ventilation of the area. **Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency. Respiratory protective device with particle filter.

Hand protection: Protective gloves.

**Eye protection:** Tightly fitting safety goggles. Ensure eye bath is by hand.

Skin protection: Protective clothing.

Environmental: No data available.

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

# 9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

State: Powder Colour: Light Grey Odour: Odourless Evaporation rate: Not applicable. Oxidising: Not applicable. Solubility in water: Slightly Soluble

# 9.2 OTHER INFORMATION

Other Information: No data available

Viscosity: Not applicable. Viscosity test method: Not applicable. Boiling point/range°C: 102 -105°C Melting point/range°C: >1300 °C. Flammability limits %: lower: Not applicable. upper: Not applicable. Flash point°C: Not applicable. Part.coeff. n-octanol/water: Not applicable. Autoflammability°C: Not applicable. Vapour pressure: Not applicable. Relative density: Not applicable. pH: Alkaline 11.5-13.

# SECTION 10: STABILITY AND REACTIVITY

## **10.1 REACTIVITY**

Reactivity: No dangerous reactions known.

# **10.2. CHEMICAL STABILITY**

Chemical stability: The product is stable as long as it is stored properly and kept dry.

**10.3 POSSIBILITY OF HAZARDOUS REACTIONS** 

Hazardous reactions: No dangerous reactions known.

# **10.4 CONDITIONS TO AVOID**

Conditions to avoid: No further relevant information available.

**10.5 INCOMPATIBLE MATERIALS** 

Materials to avoid: No further relevant information available.

**10.6 HAZARDOUS DECOMPOSITION PRODUCTS** 

Haz. decomp. products: No dangerous decomposition products known

# **SECTION 11: TOXICOLOGICAL INFORMATION**

# 11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

The product was not investigated. The statement is derived from the properties of the single components.

#### Acute toxicity:

Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification				
1317-65-3 Limestone (Calcium carbonate)				
Oral	LC50	6450 mg/kg (Rat) (RTECS Data)		
65997-15-1 Portland cement clinker				
Oral	LD50	>2000 mg/kg (Mouse) In animal studies with cement dust no acute toxicity was observed. On the basis of the available data, the classification criteria are not fulfilled.		
Dermal	LDO (no lethality)	2000 mg/kg (Rabbit) (Limit test 24h [4]) On the basis of the available data, the classification criteria are not fulfilled.		
Inhalation	LD0 (no lethality)	5 mg/m <sup>3</sup> (Rat) (Limit test [10]) On the basis of the available data, the classification criteria are not fulfilled.		
1305-62-0 Calcium dihydroxide				
Oral	LD50	7340 mg/kg (Rat) (OECD 425) >2500 mg/kg (Rabbit) (OECD 402) >2500 mg/kg (Rabbit) (OECD 402)		
Dermal	LD50	>2500 mg/kg (Rabbit) (OECD 402)		

#### SYMPTOMS / ROUTES OF EXPOSURE

Skin contact: There may be irritation and redness at the site of contact.

**Eye contact:** There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

**Other information:** No data available.

# **SECTION 12: ECOLOGICAL INFORMATION**

# **12.1 TOXICITY**

The product was not investigated. The statement is derived from the properties of the single components.

Aquatic toxicity				
1317-65-3 Limestone (Calcium carbonate)				
LC50 (96h)	>100 mg/l (Rainbow trout - oncorhynchus mykis) (OECD 203)			
LC50 (48h)	>100 mg/l (Water flea - daphnia magma) (OECD 202)			
EC50	>14 mg/l (Algae - desmodesmus subspicatus) (OECD 201) >1000 mg/l (Activated sewage sludge) (OECD 209)			
65997-15-1 Portland cement clinker				
LC50	- mg/l (Water flea - daphnia magma) (low effect [6,8]) - mg/l (Algae - selenastrum coli) (low effect [7,8]) - mg/l (Sediments) (low effect [9])			
1305-62-0 Calcium dihydroxide				
LC50 (96h seawater)	457 mg/l (Fish) 158 mg/l (Invertebrate)			
LC50 (96h freshwater)	33.884 mg/l (African catfish - clarias gariepinus) 50.6 mg/l (Fish)			
EC50 (48h)	49.1 mg/l (Invertebrate)			
EC50 (72h)	184.57 mg/l (Algae)			

# 12.2 PERSISTENCE AND DEGRADABILITY

The product is not removable from water by biological cleaning process.

**12.3 BIOACCUMULATIVE POTENTIAL** 

#### Does not accumulate in organisms.

# **12.4 MOBILITY IN SOIL**

### Slightly soluble

# Ecotoxical effects:

Only by increasing the pH value during application of large quantities.

#### 1305-62-0 Calcium dihydroxide

NOEC (72h) NOEC (14d) NOEC (21d) NOEC (26h) EC10/LC10 (NOEC)
--

48 mg/l (Algae) 32 mg/l (Invertebrate) 1080 mg/kg (General plants) 56 mg/l (Guppy - poecilia reticulata) 12000 mg/kg (Soil microorganisms) 2000 mg/kg (Soil macroorganisms)

#### Behaviour in sewage processing plants:

#### Remark:

Ecotoxicological tests with Portland cement on Daphnia magna (US EPA, 1994a, see Section 16 References [6]) and Selenastrum Coli (US EPA, 1993, see section 16

literature [7]) have shown little toxicological effect. Therefore, the LC50 and EC50 values could not be determined, see section 16 literature [8]. There were also no

toxic effects on sediments found, see section 16 literature [9]. The addition of large quantities of cement in water can cause a pH increase and thus can be toxic to

aquatic life.

# Additional ecological information:

## General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

# 12.5 RESULTS OF PBT AND vPvB ASSESSMENT

#### PBT identification: This product is not identified as a PBT/vPvB substance

# **12.6 OTHER ADVERSE EFFECTS**

No further relevant information available. **Literature** No further relevant information available

# **SECTION 13: DISPOSAL CONSIDERATIONS**

# **13.1 WASTE TREATMENT METHODS**

**Disposal operations:** Transfer to a suitable container and arrange for collection by a specialised disposal company. **Recovery operations:** No information available.

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

# **SECTION 14: TRANSPORT INFORMATION**

14.1 UN NUMBER		
ADR, ADN, IMDG, IATA	VOID	
14.2 UN PROPER SHIPPING NAME		
ADR, ADN, IMDG, IATA Class	VOID	
14.3 TRANSPORT HAZARD CLASS(ES)		
ADR, ADN, IMDG, IATA	VOID	
14.4 PACKING GROUP		
ADR, ADN, IMDG, IATA Class	VOID	
14.5 ENVIRONMENTAL HAZARDS		
Marine pollutant:	No	

#### Environmentally hazardous:

No Marine pollutant: No 14.6.

#### SPECIAL PRECAUTIONS FOR USER

Special precautions: No special precautions.

# **SECTION 15: REGULATORY INFORMATION**

# 15.1 SAFETY, HEALTH, AND ENVIRONMENTAL REGULATIONS/ LEGISLATION SPECIFIC FOR THE SUB-STANCE OR MIXTURE

#### Specific regulations: Not applicable.

# **15.2 CHEMICAL SAFETY ASSESSMENT**

# **SECTION 16: OTHER INFORMATION**

**Other information:** According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 \* indicates text in the SDS which has changed since the last revision.

#### Phrases used in s.2 and s.3:

H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H318: Causes serious eye damage.
H335: May cause respiratory irritation.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

Unit 4, Bridgegate Business Park Gatehouse Way Aylesbury HP19 8XN



0800 1337 072 info@ewipro.com www.ewipro.com

