

MT PRG (M5634 PER)
PAINTERS MASKING TAPE 21 DAY-INTERIOR



TECHNICAL DATA

TYPICAL APPLICATIONS

- > Painted walls & trims
- > Lacquered / varnished woodwork
- > Glass, plastic, metal

ADVANTAGES AND BENEFITS

- > Easy On and Easy Off
- > 21 Days clean removal
- > Sharp paint lines
- > Great conformability

CONSTRUCTION

Overall Grade: Painter's and All Purpose

Backing: High Quality Micro-Creped Paper

Adhesive: Non-Solvent, specially modified medium tack adhesive

COLOR(S)

☐ Natural

STANDARD SIZE

Width(s): 18mm/ 3.4", 24mm/1", 36mm/1.5", 48mm/2", 72mm/3"

Length(s): 55m/60yd

Contact your Dolphin sales representative for other available sizes and colors.



PHYSICAL PROPERTIES

	STANDARD VALUES	UNITS	TOLERANCE
Thickness	115	my	(+/- 10%)
Adhesion to Stainless Steel 90°	≥ 4	N/2,5cm	-
Tensile Strength	3,1	kg/cm	(+/- 2%)
Elongation	9	%	(+/- 2%)
Service Temperature Range	70	max °C	
	158	max °F	

The following properties are typical and should not be considered specifications. All properties are approximate and are based on tests believed to be reliable and performed conformance with recommended test methods. These values are presented for comparison purposes and do not represent a guarantee by the manufacturer. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.