

Unit 6, Lime Grove Est, Haverhill, Suffolk, CB9 7XU
Tel: 01440 766 975 www.lynvale.co.uk



EPDM EXT Membrane

EPDM EXT is an elastomeric waterproofing strip based on the rubber polymer EPDM with a low water vapour transmission factor. The product is used as a vapour control layer such as façade waterproofing, damp proof course or similar. The product comes in black colour and has a surface texture on both sides for maximum adhesion. EPDM EXT provides very long expected service life and is an environmental friendly product.

Technical Data

Thickness: 0.6/0.75/1.0/1.2/1.5 mm **Length:** 25 m **Width:** From 100 to 1700 mm

Weight:

0.6 mm: $0.77 \text{ kg/m2} \mid 0.75 \text{ mm}$: $0.97 \text{ kg/m2} \mid$

| 1.0 mm: 1.29 kg/m2 | 1.2 mm: 1.55 kg/m2 | 1.5 mm: 1.94 kg/m2

SD-Value:

0.6 mm: 19.2 m | 0.75 mm: 24 m | 1.0 mm: 32 m | 1.2 mm: 38,4 m | 1.5 mm: 48 m

Physical Properties

For detailed product data, please see corresponding Declaration of Performance.

Storage

Store cool and dry in the original packaging. There are no limitations in shelf life.

Approvals, Certificates & Specifications

CE EN 14909, CE EN 13984, ATG approval.

The above information is given in good faith and for guidance only. The user shall be responsible for determining that the performance of the product is sufficient for his application. The quoted values are based on averages and should not be taken as maximum or minimum values for specific purposes.