

# PRO CLEAN RENDER CLEANER

The EWI Pro render Cleaner is ideal for removing unwanted silicone render and basecoats. The unique formula breaks down any silicone render, removing it easily from windows, sills, and other unwanted areas. Pro Clean uses nano-energy cells which penetrate the render spillage and actively help's lift away.

The EWI Pro render cleaners comes in 1 & 5 litre containers, Do not dilute with water. Pro clean has been specifically formulated to work on dried and wet renders. Can also use it on cementitious products, including monocouche render and basecoats.

## Intended Uses.

The EWI Pro render Cleaner is multi-purpose and can be used on multiple surfaces. It has been designed to be used industrially, professionally and domestically, ideal for large or small surfaces. Effective on stainless steel, plastic, wood, ceramic, glass, rubber, concrete, metal, vinyl and safety floors and more.

## Directions of use

### Product preparation

EWI Pro cleaner is ready-to-use and does not require diluting.

### Application

Spray the pro cleaner onto the spillage and leave for 20 minutes. This allows the Cleaner to penetrate the product and ensure it can easily be removed. Note the spillage needs to be kept wet throughout the 20 minutes; therefore further application may need to be applied. For general cleaning leave on for 1 minute before clearing away. Use a suitable cleaning implement such as a wire brush or cloth when applying the cleaner. Agitate the area to lift the unwanted product from the surface. For stubborn spillages, repeat the process until entirely removed.

### Packaging

1Litre and 5 Litre Jerry Can

### Storage

Shelf life: up to 12 months from the date of manufacture. Store unopened, in original packaging, and a cool, dry place.

### Safety Measures

Avoid contact with the eyes. In the event of eye contact, wash the affected area with plenty of cold water as soon as possible and seek medical attention. Do not ingest. Keep out of reach of children. Refer to the material safety sheet for further information regarding first aid and protection recommendations.

Contact with render cleaner may cause irritation. For further details, refer to our Health & Safety Data Sheets.



## Technical Specification

### Use of substance/mixture

Multi-purpose, multi-surface ready to use cleaning

### Appearance /Physical state

Slightly viscous clear to slightly opaque Liquid

### Relative density

1.0 to 1.01 @ 20°C

### Solubility

Dispersible

## Application specifications

### Render Cleaner

EWI Pro clean - Render Cleaner

### Application temperature (air,substrate, materials)

from 5°C to 25°C

### Activation time

leave for 1 minute on general cleaning and up to 20 minutes for heavy stains

### Quantity to be used:

The product should cover the spilled area & be kept wet throughout the processes.

### Freezing point

-2°C

### Boiling point

100°C

### Storage conditions

Protect against frost and direct sunlight