

TECHNICAL DATASHEET

Continuous mixing pump MIXPRO 28 plaster | ref.30720



Easy-to-use continuous mixing pump with a high yield.

It can be disassembled in 4 parts, without tools, for a simplified transport.

The new 2021 version of the control panel makes the operation of the machine much more intuitive.

APPLICATIONS

Floor screed, plaster, air insulation, fireproof products, light powders (polystyrene) ...

Products with instant kneading and no need for rest time.

Tank capacity	70 L
Electrical supply	230 V - 50 Hz
Thermal protection	yes
Geared-motor driving mixing arm	2,2 kW
Compressor	yes
Compressor power	1,1 kW
Compressor air flow	13 m ³ /h
Variable speed	no
Water pump	yes
Flow-meter	digital display
Water safety switch	yes
Product pressure	0 to 20 bar
Product flow-rate	up to 26 L/min
Rotor/stator	T 26 - 16 L/min
Spraying yield	28 bags of 33 kg/h
Spraying max. hose length	20 m
Loading height	102 cm
Dimensions (l x w x h)	100 x 76 x 159 cm
Weight	120 kg
Noise level	78 Lwa

Delivered with

- a complete lance with clip-on nozzle
- a Ø25 x 15 m product hose
- a Ø19 x 2 m pouring hose
- a Ø13 x 16 m air hose with GEKA
- a water hose Ø19 x 40 m with GEKA
- an electrical cable 20 m with plug
- a platine mounted compressor
- an unplugging key
- a mixing tube cleaning part
- a mounting spray for rotor/stator
- two cleaning balls