

# **EWI-533 TANKING MEMBRANE SAFETY DATA SHEET**

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE COMPANY OR UNDERTAKING

## 1.1 Product Identifier:

EWI-533 Tanking Membrane

### 1.2 Relevant identified uses of the substance or mixture and uses advised against:

### Life cycle stages

C/PW Consumer use / Widespread use by professional workers

#### Sector of Use

SU19 Building and construction work

### **Product category**

PC1 Adhesives, sealants

### **Process category**

PROC10 Roller application or brushing
PROC11 Nonindustrial spraying
PROC19 Manual activities involving hand contact

### Environmental release category

ERC10a / ERC11a Widespread use of articles with low release

### **Article category**

AC0 Other

### Application of the substance / the preparation

Sealant - Product for an industrial, technical and private use for processing on buildings. For all other uses is advised against/ not recommended.

### 1.3 Details of the supplier of the safety data sheet:

### Manufacturer:

EWI Pro Insulation Systems Ltd

Unit 1-2, King Georges Trading Estate, Davis Road, Chessington, England, KT9 1TT

0800 133 7072 info@ewipro.com technical@ewipro.com

# Producer:


KREISEL - Technika Budowlana Sp. z o.o., ul. Szarych Szeregów 23, 60-462 Poznań, Poland

Tel. +48 (0)61 846 79 00 Fax +48 (0)61 846 79 09 poznan@kreisel.pl

kreisel.pl

### 1.4 Emergency phone number:

Environment Agency Emergency Hotline: +44/(0)800 80 70 60 Emergency Services (UK): 999





















### **SECTION 2: HAZARDS IDENTIFICATION**

### 2.1 Classification of the substance or mixture:

### Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the GB CLP regulation.

### 2.2 Label elements

### Labelling According to Regulation (EC) No 1272/2008 (CLP)

Void

### **Hazard pictograms**

Void

### Signal word

Void

#### **Hazard statements**

Void

### Additional information:

EUH208 Contains 1,2-Benzisothiazol-3(2H)-one, 2-Methyl-2H-isothiazol-3-one. May produce an allergic reaction. EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Contains the following biocidal active ingredients to protect the product. Please note the information in the safety data sheet and the legal regulations: BIT,

### 2.3 Other hazards

No further relevant information available.

### Results of PBT and vPvB assessment

**PBT:** This substance/mixture contains no components classified as persistent, bioaccumulative and toxic (PBT) at levels of 0.1% or higher. **vPvB:** This substance/mixture contains no components classified as very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## Determination of endocrine-disrupting properties

This substance/mixture does not contain components with endocrine disrupting properties according to the criteria of Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentrations of 0.1% or higher.

# **SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS**

### 3.1 Chemical characterization: Substances

This product is a mixture.

### 3.2 Mixtures

### **Description:**

Revision: 1.0

Review Date: 11/09/2025

Mixture of acrylat dispersion and fillers with non-hazardous additions.



















Dangerous components:		
CAS: 13463-67-7	Titanium dioxide (≥ 1% particles ≤ 10µm)	
EINECS: 236-675-5	Substance with a Community workplace	1 - 2.5%
Index number: 022-006-00-2	exposure limit	
REACH: 01-2119489379-17		
CAS: 2634-33-5	1,2-Benzisothiazol-3(2H)-one:	< 0.025%
EINECS: 220-120-9	Acute Tox. 2, H330; Eye Dam. 1, H318;	
Index number: 613-088-00-6	Aquatic Acute 1, H400; Aquatic Chronic 1, H410;	
REACH: 01-2120761540-60	Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens.	
	1A, H317	
	ATE: LD <sub>50</sub> oral: 450 mg/kg	
	Specific concentration limit:	
	Skin Sens. 1A; H317: C ≥0.036 %	
CAS: 2682-20-4	2-Methyl-2H-isothiazol-3-one:	< 0.0015%
EINECS: 220-239-6	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute	
REACH: 01-2120764690-50	Tox. 2, H330; Skin Corr. 1B, H314; Eye Dam. 1,	
	H318; Aquatic Chronic 1, H410; Skin Sens. 1, H317	
	Specific concentration limit:	
	Skin Sens. 1; H317: C ≥0.0015 %	

Other components (>20%):		
CAS: 7732-18-5	Water	25 - 50%
EINECS: 231-791-2		
REACH: 1		
CAS: 1317-65-3	Limestone (Calcium carbonate)	25 - 50%
EINECS: 215-279-6	Consisting of: 471-34-1 Calcium carbonate (>	
REACH: 1	90%); 16389-88-	
	1 Calcium/Magesium carbonate (0 - 10%); 14808-	
	60-7 Quartz	
	$(SiO_2)$ (0 - 10%); 37244-96-5 Feldspar (0 - 5%);	
	12001-26-2	
	Mica - Potassium aluminum silicate (Muscovite)	
	(0 - 5%)	
EC number: 920-793-5	Styrene acrylates copolymer	25 - 50%
REACH: 1		

### Additional information:

For the wording of the listed hazard phrases refer to section 16.

Note 10 (EU 2020/217): The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\le$  10  $\mu$ m.

<sup>1</sup> Not subject to registration in accordance with EC 1907/2006 Annex V (point 7) or Article 2.

# **SECTION 4: FIRST AID MEASURES**

# 4.1 Description of first aid measures:

### General information:

For first responder no special personal protective equipment is required. First responder should avoid contact with the product.

# After inhalation:

Take affected persons into fresh air and keep quiet. Seek medical treatment in case of complaints. In case of irregular breathing or respiratory arrest provide artificial respiration. In case of unconsciousness place patient stably in side position for transportation.



















#### After skin contact:

Immediately wash with water and soap and rinse thoroughly. Immediately remove all soiled and contaminated clothing. Wash contaminated clothes before reuse. Clean contaminated shoes before reuse. If skin irritation continues, consult a doctor.

#### After eye contact:

Do not rub eyes because additional damage to eyes can be caused by mechanical stress. If necessary, remove contact lenses and flush the eye immediately while holding eyelids open to water for at least 20 minutes. If possible, isotonic eyewash solution (e. g. 0,9% NaCl). Always consult an occupational physician or ophthalmologist.

#### After swallowing:

Do not induce vomiting. If conscious rinse mouth with water and drink plenty of water. Consult a physician or poison control centre.

### 4.2 Main symptoms and effects, acute and delayed:

Symptoms and effects are described in section 2 and 11.

#### Hazards:

No further relevant information available.

#### 4.3 Indications for medical attention and special treatments to be administered immediately:

If a physician is to be consulted, as per possibility he should be presented this safety data sheet.

### **SECTION 5: FIRE-FIGHTING MEASURES**

### 5.1 Extinguishing media:

The mixture is flammable neither in the delivery condition not in mixed conditions. Extinguisher and firefighting are therefore adjusted to the surrounding fire.

### Suitable extinguishing agents:

The mixture is flammable neither in the delivery condition not in mixed conditions. Extinguisher and firefighting are therefore adjusted to the surrounding fire.

### 5.2 Specific hazards arising from the mixture:

This product is neither explosive nor flammable, and non-oxidizing with other materials. Particular danger of slipping on leaked/spilled product.

### 5.3 Advice for firefighters:

No special measures required. Collect contaminated firefighting water separately. It must not enter the sewage system. Dispose of fire debris and contaminated firefighting water in accordance with official regulations.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### 6.1 Personal Precautions, Protective Equipment and Emergency Procedures:










Respiratory protection: Use suitable respiratory protective device only when aerosol or mist is formed (FFP2 according to EN 149)





















Hand protection: Chemical resistant protective gloves according EN ISO 374

Eye/face protection: In case of splash risk use tightly fitting safety goggles according to EN 166.

Body protection: Protective work clothing

If appropriate, reference must be made to exposure controls and personal protection (see section 8).

### 6.2 Precautions for the environment:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

### 6.3 Methods and material for containment and cleaning:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of the material collected according to regulations.

### 6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: HANDLING AND STORAGE**

### 7.1 Precautions for Safe Handling:

Ensure good ventilation/exhaustion at the workplace. Avoid contact with the eyes and skin. Wear protective clothing. Washing facilities / Water for cleaning yes and skin should be available. Persons, who tend to skin diseases or other hypersensitivity reactions of the skin, should not handle the product. Do not eat, drink, smoke or sniff while working.

# Information about fire - and explosion protection:

No special measures required.

# 7.2 Conditions for safe storage, including any incompatibilities

### Requirements to be met by storerooms and receptacles:

Keep out of reach of children. Store in cool, dry place in tightly closed receptacles.

### Information about storage in one common storage facility:

Keep away from foodstuffs, beverages and feed.

## Further information about storage conditions:

Protect from frost. Protect from heat and direct sunlight.

# Miniumum storage life:

Minimum storage life (+5°C up to 25°C): See indication on package.

Storage class: 12

### 7.3 Specific end use(s)

No further relevant information available.



















# **SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION**

# 8.1 Control parameters:

Ingredients with limit values that require monitoring at the workplace:		
13463-67-7 Titanium dioxide (≥ 1% particles ≤ 10 μm)		
WEL (Great Britain)	Long-term value: 10* 4** mg/m³	
	*total inhalable **respirable	

DNELs		
13463-67-7 Titanium dioxide (	≥ 1% particles ≤ 10μm)	
Oral	Long term exposure	700 mg/kg bw/d (Consumer)
Inhalative	Systemic - Long term exposure	10 mg/m³ (Employee)
2634-33-5 1,2-Benzisothiazol-	3(2H)-on	
Dermal	Systemic - Long term exposure	0.345 mg/kg bw/d (Consumer)
		0.966 mg/kg bw/d (Employee)
Inhalative	Systemic - Long term exposure	1.2 mg/m³ (Consumer)
		6.81 mg/m³ (Employee)
2682-20-4 2-Methyl-2H-isoth	iazol-3-one	
Oral	Long term exposure	0.027 mg/kg bw/d (Consumer)
	Short term exposure	0.053 mg/kg bw/d (Consumer)
Inhalative	Local - Long term exposure	0.021 mg/m³ (Consumer)
		0.021 mg/m³ (Employee)
	Local - Short term exposure	0.34 mg/m³ (Consumer)
	·	0.34 mg/m³ (Employee)

PNECs		
13463-67-7 Titanium dioxide (≥ 1% particles ≤ 10μm)		
Freshwater	0.127 mg/l	
Marine water	1 mg/I	
Soil	> 100 mg/kg	
Sediments (Freshwater)	> 1,000 mg/kg	
Sediments (Marine water)	100 mg/kg	
Sewage plant	100 mg/l	
2634-33-5 1,2-Benzisothiazol-3(2H)-one		
Freshwater	0.00403 mg/l (not specified)	
Marine water	0.000403 mg/I (not specified)	
Soil	3 mg/kg (not specified)	
Sediments (Freshwater)	0.0499 mg/kg (not specified)	
Sediments (Marine water)	0.000499 mg/kg (not specified)	
Sewage plant	1.03 mg/I (not specified)	
2682-20-4 2-Methyl-2H-isothiazol-3-one		
Freshwater	0.00339 mg/l (not specified)	
Soil	0.047 mg/kg (not specified)	
Sediments (Marine water)	0.00339 mg/kg (not specified)	
Sewage plant	0.23 mg/l (not specified)	

# Ingredients with biological limit values:

Void

# Additional information:

The lists valid during the making were used as basis.



















#### 8.2 Exposure controls:

### 8.2.1. Appropriate technical controls:

No further data; see item 7.

### 8.2.2. Individual protective measures, such as personal protective equipment:

### General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Remove contaminated clothing immediately and thoroughly clean it before using it again. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection. Ensure that washing facilities are available at the workplace.

#### **Respiratory protection:**

Use suitable respiratory protective device only when aerosol or mist is formed (FFP2 according to EN 149)

#### Hand protection:

Hand protection: Chemical resistant protective gloves according EN ISO 374 The glove material has to be impermeable and resistant to the product. Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times rates of diffusion and the degradation. Check protective gloves prior to each use for their proper condition. Preventive skin protection by use of skinprotecting agents is recommended. To avoid skin problems, reduce the wearing of gloves to the required minimum.

### Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

### For the permanent contact gloves made of the following materials are suitable:

- Polychloroprene (material thickness ≥ 0.5 mm; breakthrough time ≥ 480 min.)
- Nitrile rubber (material thickness ≥ 0.35 mm; breakthrough time ≥ 480 min.)
- Butyl rubber (material thickness ≥ 0.5 mm; breakthrough time ≥ 480 min.)
- Fluororubber (material thickness ≥ 0.4 mm; breakthrough time ≥ 480 min.)
- Neoprene (material thickness ≥ 0.5 mm; breakthrough time ≥ 480 min.)

### Not suitable are gloves made of the following materials:

Non-liquid-tight gloves made of fabric, leather or similar materials.

### Eye/face protection:

In case of splash risk use tightly fitting safety goggles according to EN 166.

### **Body protection:**

Protective work clothing

### Risk management measures:

An operator training/guidance in the correct use of personal protective equipment is necessary to ensure the required level of effectiveness.

# 8.2.3. Environmental exposure controls:

Avoid release in the environment. Use the surplus or dispose it of properly.



















# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

## 9.1 Information on Basic Physical and Chemical Properties:

### **General Information**

⇒ Physical state Liquid

# Appearance:

- → Form: Pasty
- ⇒ Colour: Light blue
- → Odour: Mild
- → Odour threshold: Not safety relevant
- ⇒ pH at 20 °C (68 °F) 8 10: Saturated aqueous solution

### Change in condition

- → Melting point/freezing point: ~ 0 °C (~ 32 °F) (ISO 3016)
- ➡ Boiling point or initial boiling point and boiling range 100 °C (212 °F)
- ➡ Flammability Product is not flammable.
- ➡ Flash point: Not applicable
- → Auto-ignition temperature: > 400 °C (> 752 °F) (DIN 51794)
- ➡ Decomposition temperature: > 825°C to CaO and CO<sub>2</sub>
- → Oxidising properties: None
- ightharpoonup Explosive properties: Product does not present an explosion hazard.

Lower and upper explosion limit

- → Lower: Not determined
- → Upper: Not determined
- ⇒ Ignition temperature: Product is not selfigniting.
- → Vapour pressure at 20 °C (68 °F): 23 hPa (17.3 mm Hg)

Density and/or relative density

→ Density at 20 °C (68 °F): 1.4 - 1.6 g/cm³ (11.68 - 13.35 lbs/gal)

### Particle size

## **Viscosity:**

→ Dynamic at 20 °C (68 °F): > 1,000 mPas (DIN 53019)

# Solubility

- → Water: Not miscible or difficult to mix
- → Partition coefficient n-octanol/water (logvalue) Not determined





















→ Solids content: 60 - 64 %

### Solvent content:

- ➡ Organic solvents: 0.5 %
- → VOC without water (EC): 15.66 21.66 g/I
- → VOC with water (EC): 7.06 8.07 g/I
- → VOC with water (EC): 0.504 %

### 9.2 Other information

Information with regard to physical hazard classes

- ⇒ Explosives Void
- ⇒ Flammable gases Void
- → Aerosols Void
- → Oxidising gases Void
- ➡ Gases under pressure Void
- ➡ Flammable liquids Void
- → Flammable solids Void
- ⇒ Self-reactive substances and mixtures Void
- ⇒ Pyrophoric liquids Void
- ⇒ Pyrophoric solids Void
- ightharpoonup Self-heating substances and mixtures Void
- ightharpoonup Substances and mixtures, which emit flammable gases in contact with water Void
- → Oxidising liquids Void
- → Oxidising solids Void
- → Organic peroxides Void
- → Corrosive to metals Void
- ⇒ Desensitised explosives Void


# **SECTION 10: STABILITY AND REACTIVITY**

# 10.1 Reactivity:

No dangerous reactions known.

# 10.2 Chemical stability:

The product is stable as long as it is stored properly and dry.





















### Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

### 10.3 Possibility of hazardous reactions:

No dangerous reactions known.

### 10.4 Conditions to avoid:

No further relevant information available.

### 10.5 Incompatible materials:

No further relevant information available.

### 10.6 Hazardous decomposition products:

No dangerous decomposition products known.

#### Minimum storage life:

Minimum storage life (+5°C up to 25°C): See indication on package.

### **Additional information:**

No further relevant information available.

# **SECTION 11: TOXICOLOGICAL INFORMATION**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

The product was not investigated. The statement is derived from the properties of the single components.

### **Acute toxicity:**

Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification: 1317-65-3 Limestone (Calcium carbonate)		
Styrene acrylates copolymer		
Oral	LD <sub>50</sub>	> 5,000 mg/kg (Rat)
Dermal	LD <sub>50</sub>	> 5,000 mg/kg (Rat)
13463-67-7 Titanium dioxide (2	1% particles ≤ 10μm)	
Oral	LD <sub>50</sub>	> 5,000 mg/kg (Rat) (OECD 425)
	Carcinogenicity	(Mouse) (ECHA Registration dossier)
		no effects observed
Dermal	LD <sub>50</sub>	> 5,000 mg/kg (Rabbit)
2634-33-5 1,2-Benzisothiazol-3	S(2H)-one	
Oral	LD <sub>50</sub>	450 mg/kg (ATE)
		1,150 mg/kg (Mouse)
		597 mg/kg (Rat)
Dermal	LD <sub>50</sub>	> 2,000 mg/kg (Rat)
Inhalative	LC <sub>50</sub> (4h)	0.05 mg/I (ATE)
2682-20-4 2-Methyl-2H-isothic	azol-3-one	
Oral	LD <sub>50</sub>	232 - 249 mg/kg (Rat) (OECD 401)
Dermal	LD <sub>50</sub>	242 mg/kg (Rat) (OECD 402)
Inhalative	LC <sub>50</sub> (4h)	0.05 mg/I (ATE)
	LC <sub>50</sub> (4h)	0.11 mg/l (Rat) (OECD 403)

















Other information (about experimental toxicology):  13463-67-7 Titanium dioxide (≥ 1% particles ≤ 10µm)		
Irritation of skin	OECD 404 (skin)	(Rabbit) not corrosive
Irritation of eyes	OECD 405 (eye)	(Rabbit) not irritant
Sensitisation	OECD 429 (LLNA)	(Mouse) not sensitizing
	OECD 421 (Reproduction screening test)	(Rat) no effects observed
2682-20-4 2-Methyl-2H-isothia	zol-3-one	
Oral	OECD 408 (Repeated dose oral toxicity 90d)	19 mg/kg bw/day (Rat)
Irritation of skin	OECD 404 (skin)	(Rabbit) Corrosive
Sensitisation	OECD 406 (sensitization)	(Guinea pig) sensitizing

### Primary irritant effect:

#### On the skin:

Based on available data, the classification criteria are not met.

### On the eye:

Based on available data, the classification criteria are not met.

### Sensitization:

Sensitising effect by skin contact is possible by prolonged exposure.

Based on available data, the classification criteria are not met.

### Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

### Carcinogenicity:

Based on available data, the classification criteria are not met.

### Reproductive toxicity:

Based on available data, the classification criteria are not met.

# Specific target organ toxicity - single exposure (STOT SE):

Based on available data, the classification criteria are not met.

### Specific target organ toxicity - repeated exposure (STOT RE):

Based on available data, the classification criteria are not met.

### **Aspiration hazard:**

Based on available data, the classification criteria are not met.

# Practical experience

No further relevant information available.

### **General comments**

No further relevant information available.

### 11.2 Information on other hazards

### **Endocrine disrupting properties**

None of the ingredients is listed.

















# **SECTION 12: ECOLOGICAL INFORMATION**

### 12.1 Toxicity:

The product was not investigated. The statement is derived from the properties of the single components.

Aquatic toxicity:	
1317-65-3 Limestone (Calcium carbonate)	
LC <sub>50</sub> (96h)	> 100 mg/I (Rainbow trout - oncorhynchus mykis) (OECD 203)
LC <sub>50</sub> (48h)	> 100 mg/I (Water flea - daphnia magma) (OECD 202)
EC <sub>50</sub>	> 14 mg/l (Algae - desmodesmus subspicatus) (OECD 201)
	> 1,000 mg/l (Activated sewage sludge) (OECD 209)
Styrene acrylates copolymer	
LC <sub>50</sub> (96h)	> 100 mg/l (Zebrafish - danio rerio)
EC <sub>50</sub> (48h)	> 100 mg/l (Water flea - daphnia magma)
EC <sub>50</sub> (72h)	> 100 mg/l (Algae - desmodesmus subspicatus)
13463-67-7 Titanium dioxide (≥ 1% particles ≤ 10μm)	
LC <sub>50</sub> (48h)	5.5 mg/l (Water flea - daphnia magma)
LC <sub>50</sub> (96h Marine water)	> 10,000 mg/l (Fish)
LC <sub>50</sub> (96h Freshwater) (static)	> 100 mg/l (Goldfish) (OECD 203)
EC <sub>50</sub> (48h)	> 1,000 mg/l (Water flea - daphnia magma) (ASTM Standard E729)
EC <sub>50</sub> (72h)	5.83 mg/l (Algae - pseudokirchneriella subcapitata)
EC <sub>50</sub> (3h)	> 1,000 mg/l (Activated sludge organisms) (OECD 209)
EC <sub>50</sub> (7d)	> 100 mg/l (Lemna minor) (OECD 221)
NOEC (48h)	1 mg/l (Water flea - daphnia magma)
NOEC (21d)	> 10 mg/kg (Water flea - daphnia magma) (OECD 202)
NOEC (28d) (static)	> 100 mg/l (Chironomus riparius) (OECD 219) Soil
NOEC (32d)	> 1 mg/l (Algae - scenedesmus quadricauda)
NOEC (8d)	> 1,000 mg/l (Zebrafish - danio rerio) (OECD 212)
2634-33-5 1,2-Benzisothiazol-3(2H)-one	
LC <sub>50</sub> (96h)	1.6 mg/l (Rainbow trout - oncorhynchus mykis) (OECD 203)
EC <sub>50</sub> (48h)	3.27 mg/l (Water flea - daphnia magma)
	1.5 mg/l (Water flea - daphnia)
EC <sub>50</sub> (72h)	0.11 mg/l (Algae - selenastrum capricornutum) (OECD 201)
	2 mg/l (Algae scenedesmus subcapitatus)
EC <sub>50</sub> (16h)	0.4 mg/I (Pseudomonas putida)
EC <sub>10</sub> (72h)	0.04 mg/l (Algae - selenastrum capricornutum) (OECD 201)
NOEC (21d)	1.2 mg/l (Water flea - daphnia magma) (OECD 202)
NOEC (28d)	0.21 mg/l (Rainbow trout - oncorhynchus mykis) (OECD 215)
2682-20-4 2-Methyl-2H-isothiazol-3-one	
LC <sub>50</sub> (96h Marine water) 2.98 mg/l (Water flea - daphnia magma)	
LC <sub>50</sub> (96h Freshwater) 0.934 mg/l (Water flea - daphnia magma)	
LC <sub>50</sub> 4.77 mg/I (Fish) (OECD 203)	
EC <sub>10</sub>	0.044 mg/l (Water flea - daphnia magma) (OECD 211)
	4.93 mg/l (Fish)
EC <sub>50</sub>	41 mg/l (Activated sewage sludge) (OECD 209)
	0.103 mg/l (Algae - pseudokirchneriella subcapitata) (OECD 201)
EC <sub>50</sub> (16h)	2.3 mg/l (Pseudomonas putida)



















### 12.2 Persistence and degradability:

A part of the components is biodegradable.

Degree of elimination:	
2634-33-5 1,2-Benzisothiazol-3(2H)-one	
Biodegradation	> 70 % (Activated sewage sludge) (OECD 303 A)
	> 90 % (not specified) (OECD 302 B)

### 12.3 Bioaccumulative potential:

2634-33-5 1,2-Benzisothiazol-3(2H)-one	
Log Kow	0.7 (not specified) (OECD 117)

Bioconcentration factor (BCF)	
2634-33-5 1,2-Benzisothiazol-3(2H)-one	
Bioconcentration factor (BCF)	6.95 (not specified) (OECD 305)

### 12.4 Soil mobility:

No further relevant information available.

### 12.5 PBT and vPvB assessment results:

PBT: This substance/mixture contains no components classified as persistent, bioaccumulative and toxic (PBT) at levels of 0.1% or higher.

vPvB: This substance/mixture contains no components classified as very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# 12.6 Endocrine disrupting properties

This substance/mixture does not contain components with endocrine disrupting properties according to the criteria of Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentrations of 0.1% or higher.

# 12.7 Other adverse effects:

### Literature

No further relevant information available.

### **Ecotoxical effects:**


No further relevant information available.

Behaviour in sewage processing plants:	
Styrene acrylates copolymer	
EC <sub>20</sub> (0,5h)	> 100 mg/I (Activated sludge organisms)
2634-33-5 1,2-Benzisothiazol-3(2H)-one	
EC <sub>20</sub> (0,5h)	3.3 mg/l (Activated sludge organisms) (OECD 209)
EC <sub>20</sub> (3h)	3.3 mg/I (Activated sludge organisms) (OECD 209)
EC <sub>50</sub> (3h)	13 mg/I (Activated sludge organisms) (OECD 209)
OECD 302 B Zahn Wellens Test	90 % (Activated sludge organisms) (OECD 302)
OECD 303 A Activated Sludge Units	% (Rat)
	> 70 % (Activated sludge organisms) (OECD 303 A)
2682-20-4 2-Methyl-2H-isothiazol-3-one	
EC <sub>20</sub> (3h)	2.8 mg/l (Activated sludge organisms) (DIN 38412-3 TTC-Test)

# Additional ecological information:

### General notes:

Not hazardous for water.





















## **SECTION 13: DISPOSAL CONSIDERATION**

### 13.1 Waste treatment methods

### **Recommendation:**





Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Dispose of contents/container in accordance with local/regional/national/international regulations.

European waste catalogue		
08 01 20	Aqueous suspensions containing paint or varnish other than those mentioned in 08 01 19	
17 09 04	Mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03	
15 01 02	Plastic packaging	

17 09 04 for the setted product

08 01 20 for residues of the unprocessed product

15 01 02 for the completely emptied packaging

### **Uncleaned packaging**

### Recommendation:

Disposal must be made according to official regulations.

Recycle only completely emptied packaging.

# **SECTION 14: TRANSPORT INFORMATION**

14.1. UN Number:


ADR, ADN, IMDG, IATA Void

14.2. Proper Shipping Name:

ADR, ADN, IMDG, IATA Void

14.3. Transport Hazard Class(es):

ADR, ADN, IMDG, IATA Class Void





















14.4. Packing Group:

ADR, IMDG, IATA Void

14.5. Environmental Hazards:

Marine pollutant: No

14.6. Special Precautions for User:

Not applicable

14.7. Transport in Bulk According to MARPOL Annex II and the IBC Code:

Not applicable

**UN "Model Regulation":** Void

# **SECTION 15: REGULATORY INFORMATION**

15.1 Regulations and legislation on health, safety, and environment specific to the mixture:

**Poisons Act** 

Regulated explosives precursors

None of the ingredients is listed.

**Regulated poisons** 

None of the ingredients is listed.

Reportable explosives precursors			
7631-99-4 Sodiu	dium nitrate	Listed	

Reportable poisons				
1310-73-2	Sodium hydroxide	12% of total caustic alkalinity		
50-00-0	Formaldehyde	5%		

# Directive 2004/42/EC

IIA(g) 30 - this product contains < 30 g/I VOC (see chapter 9)

Product type: PAINTS AND VARNISHES

- Product subcategory: Primers
- Water-borne coatings, Limit value: 30 g/l

**Directive (EU) 2012/18** 

Named dangerous substances - ANNEX I:

None of the ingredients is listed.

National regulations:

Waterhazard class:

Generally not hazardous for water

### Other regulations, limitations and prohibitive regulations:

• Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (UK REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing



















Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/ EC and 2000/21/EC

- Commission Regulation (EU) No 878/2020 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (UK REACH)
- Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006
- Regulation (EC) No 1013/2006 of the European Parliament and of the Council of 14 June 2006 on shipments of waste
- Regulation (EC) No 528/2012 of the European Parliament and of the Council of 22 May 2012 concerning the making available on the market and
  use of biocidal products

#### 15.2 Chemical Safety Assessment:

A Chemical Safety Assessment has not been carried out.

### **SECTION 16: OTHER INFORMATION**

#### **Relevant phrases:**

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

### **Advice for instructions:**

Additional trainings, which go beyond the prescribed training in activities involving hazardous substances are not required.

## Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

MAK: Maximale Arbeitsplatz-Konzentration (maximum concentration of a chemical substance in the workplace, Austria/Germany)

PBT: persistent, bioaccumulative and toxic properties

vPvB: very persistent, bioaccumulatice properties

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

















LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 2: Acute toxicity - Category 2

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

The information provided in this datasheet is based on the data available to us at the date of its publication.

It is the user's responsibility to take appropriate precautionary measures and apply the recommendations described previously. The information presented in this datasheet should not be considered exhaustive.

Any use of the product not specified in the instructions on the packaging, our website, or other documents provided by our company is entirely the responsibility of the user.













