

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Trade name:****EWIPRO EWI-076 PREMIUM BIO SILICONE RENDER****1.2 Relevant identified uses of the substance or mixture and uses advised against****Life cycle stages**

C/PW Consumer use / Widespread use by professional workers

Sector of Use

SU19 Building and construction work

Product category

PC9a Coatings and paints, thinners, paint removers

Process category

PROC10 Roller application or brushing

PROC11 Non industrial spraying

PROC19 Manual activities involving hand contact

Environmental release category

ERC10a / ERC11a Widespread use of articles with low release

Article category

AC0 Other

Application of the substance / the preparation

Structural skim - Product for an industrial, technical and private use for coating building surfaces.
For all other uses is advised against/ not recommended.

1.3 Details of the supplier of the safety data sheet**Manufacturer/Supplier:****Supplier:**

EWI Pro Insulation Systems LTD
Unit 1, Kingston Business Centre
Fullers Way South
Chessington, KT9 1DQ
United Kingdom

Manufacturer:

KREISEL - Technika Budowlana Sp. z o.o.
ul. Szarych Szeregów 23
60-462 Poznań
Poland

Tel.: +44 (0)800 1337072

Fax: -

Mail: info@ewipro.comWeb: www.ewipro.com

Tel.: +48 61 846 79 00

Fax: +48 61 846 79 09

Mail: poznan@kreisel.plWeb: www.kreisel.pl**Further information obtainable from:**

Product safety department (on working days 8:00 - 16:00)

1.4 Emergency telephone number

National poisons information centre: +44/(0)171 - 635 9191
National Health Service: 111
European emergency call: 112

EWIPRO EWI-076 PREMIUM BIO SILICONE RENDER

(Contd. of page 1)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

The product is not classified, according to the GB CLP regulation.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

Void

Hazard pictograms

Void

Signal word

Void

Hazard statements

Void

Additional information:

EUH208 Contains 2-Methyl-2H-isothiazol-3-one, 2-Octyl-2H-isothiazol-3-one, 4,5-dichloro-2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Contains the following biocidal active ingredients to protect the product. Please note the information in the safety data sheet and the legal regulations: MIT, OIT, DCOIT

2.3 Other hazards

No further relevant information available.

Regulation (EC) No 2055/2023 on the restriction of microplastics

The product contains $\geq 0.01\%$ microplastic particles according to Regulation EU 2023/2055. When processed as intended, these particles are immobilised in a solid matrix or are modified in such a way that they no longer fall under the definition of microplastics. Follow the manufacturer's instructions for use and disposal to avoid releasing the product into the environment. Process leftover product and allow it to harden. Recycle or dispose of the cured residues in accordance with the applicable regulations. Collect the water from the cleaning tools and reuse it or dispose of it in the local sewage system. Do not allow cleaning water to enter the environment.

Results of PBT and vPvB assessment**PBT:**

This substance/mixture contains no components classified as persistent, bioaccumulative and toxic (PBT) at levels of 0.1% or higher.

vPvB:

This substance/mixture contains no components classified as very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients**3.1 Chemical characterization: Substances**

This product is a mixture.

(Contd. on page 3)

GB













EWIPRO EWI-076 PREMIUM BIO SILICONE RENDER

(Contd. of page 2)

3.2 Mixtures
Description:

Mixture of acrylat dispersion and fillers with nonhazardous additions.

Dangerous components:

CAS: 13463-67-7 EINECS: 236-675-5 Index number:... 022-006-00-2 REACH: 01-2119489379-17	Titanium dioxide ($\geq 1\%$ particles $\leq 10\mu\text{m}$) Substance with a Community workplace exposure limit	1 - 2.5%
CAS: 2682-20-4 EINECS: 220-239-6 REACH: 01-2120764690-50	2-Methyl-2H-isothiazol-3-one  Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330;  Skin Corr. 1B, H314; Eye Dam. 1, H318;  Aquatic Chronic 1, H410;  Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317: C $\geq 0.0015\%$	< 0.0015%
CAS: 26530-20-1 EINECS: 247-761-7 Index number:... 613-112-00-5 REACH: 01-2120768921-45	2-Octyl-2H-isothiazol-3-one  Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330;  Skin Corr. 1, H314; Eye Dam. 1, H318;  Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100);  Skin Sens. 1A, H317, EUH071 ATE: LD ₅₀ oral: 125 mg/kg LD ₅₀ dermal: 311 mg/kg Specific concentration limit: Skin Sens. 1A; H317: C $\geq 0.0015\%$	$\geq 0.00025 - < 0.0015\%$
CAS: 64359-81-5 EINECS: 264-843-8 Index number:... 613-335-00-8 REACH: ²	4,5-dichloro-2-octyl-2H-isothiazol-3-one  Acute Tox. 2, H330;  Skin Corr. 1C, H314;  Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100);  Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071 ATE: LD ₅₀ oral: 567 mg/kg Specific concentration limits: Skin Irrit. 2; H315: C $\geq 0.025\%$ Eye Irrit. 2; H319: C $\geq 0.025\%$ Skin Sens. 1A; H317: C $\geq 0.0015\%$	$\geq 0.00025 - < 0.0015\%$

Other components (>20%):

CAS: 1317-65-3 EINECS: 215-279-6 REACH: ¹	Limestone (Calcium carbonate) Consisting of: 471-34-1 Calcium carbonate (> 90%); 16389-88-1 Calcium/Magesium carbonate (0 - 10%); 14808-60-7 Quartz (SiO ₂) (0 - 10%); 68476-25-5 Feldspar-group minerals (0 - 5%); 12001-26-2 Mica-group minerals (0 - 5%)	50 - < 100%
--	--	-------------

Additional information:

For the wording of the listed hazard phrases refer to section 16.

Note 10 (EU 2020/217): The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10\mu\text{m}$.

¹ Not subject to registration in accordance with EC 1907/2006 Annex V (point 7) or Article 2.

GB

(Contd. on page 4)

EWIPRO EWI-076 PREMIUM BIO SILICONE RENDER

(Contd. of page 3)

SECTION 4: First aid measures**4.1 Description of first aid measures**

First aid

General information:

For first responder no special personal protective equipment is required. First responder should avoid contact with the product.

After inhalation:

Take affected persons into fresh air and keep quiet. Seek medical treatment in case of complaints. In case of irregular breathing or respiratory arrest provide artificial respiration. In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly. Immediately remove all soiled and contaminated clothing. Wash contaminated clothes before reuse. Clean contaminated shoes before reuse. If skin irritation continues, consult a doctor.

After eye contact:

Do not rub eyes because additional damage to eyes can be caused by mechanical stress. If necessary, remove contact lenses and flush the eye immediately while holding eyelids open to water for at least 20 minutes. If possible, isotonic eyewash solution (e. g. 0,9% NaCl). Always consult an occupational physician or ophthalmologist.

After swallowing:

Do not induce vomiting. If conscious rinse mouth with water and drink plenty of water. Consult a physician or poison control center.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are described in section 2 and 11.

Hazards:

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

If a physician is to be consulted, as per possibility he should be presented this safety data sheet.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

The mixture is flammable neither in the delivery condition not in mixed conditions. Extinguisher and fire fighting are therefore adjusted to the surrounding fire.

Suitable extinguishing agents:

The mixture is flammable neither in the delivery condition not in mixed conditions. Extinguisher and fire fighting are therefore adjusted to the surrounding fire.

5.2 Special hazards arising from the substance or mixture

This product is neither explosive nor flammable, and non-oxidizing with other materials. Particular danger of slipping on leaked/spilled product.

5.3 Advice for firefighters

No special measures required. Collect contaminated fire fighting water separately. It must not enter the sewage system. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

GB

(Contd. on page 5)

EWIPRO EWI-076 PREMIUM BIO SILICONE RENDER

(Contd. of page 4)

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

If appropriate, reference must be made to exposure controls and personal protection (see section 8).

6.2 Environmental precautions

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling:**

Ensure good ventilation/exhaustion at the workplace. Avoid contact with the eyes and skin. Wear protective clothing. Washing facilities / Water for cleaning yes and skin should be available. Persons, who tend to skin diseases or other hypersensitivity reactions of the skin, should not handle the product. Do not eat, drink, smoke or sniff while working.

The product must be stored in its original packaging and protected from the effects of weather and soil moisture. When opening the packaging, make sure that the product does not spill and only gets into the equipment intended for processing. Cover the work surface with a suitable tarpaulin. Apply the product according to the instructions in the technical data sheet. Avoid aerosol formation during machine application and avoid spilling the product. Process product residues and allow them to harden. Cured product residues must be disposed of in accordance with national regulations.

Remove product residues from the mixing systems and tools before cleaning them with water. Do not allow cleaning water to enter the environment. Collect the cleaning water and allow the solid components to settle. The excess water can then be reused or disposed of in the public sewage system. Allow the settled components to harden and dispose of them in accordance with national regulations. Cleaning with high-pressure cleaners is not recommended as this could lead to the product being released into the environment.

Information about fire - and explosion protection:

No special measures required.

7.2 Conditions for safe storage, including any incompatibilities**Requirements to be met by storerooms and receptacles:**

Keep out of reach of children. Store in cool, dry place in tightly closed receptacles.

Information about storage in one common storage facility:

Keep away from foodstuffs, beverages and feed.

Further information about storage conditions:

Protect from frost. Protect from heat and direct sunlight.

Minimum storage life:

Minimum storage life (+5°C up to 25°C): See indication on package.

Storage class: 12

(Contd. on page 6)

EWIPRO EWI-076 PREMIUM BIO SILICONE RENDER

(Contd. of page 5)

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Ingredients with limit values that require monitoring at the workplace:
13463-67-7 Titanium dioxide ($\geq 1\%$ particles $\leq 10\mu\text{m}$)

WEL (Great Britain)	Long-term value: $10^* 4^{**} \text{ mg/m}^3$ *total inhalable **respirable
---------------------	--

DNELs
13463-67-7 Titanium dioxide ($\geq 1\%$ particles $\leq 10\mu\text{m}$)

Oral	Long term exposure	700 mg/kg bw/d (Consumer)
Inhalative	Systemic - Long term exposure	10 mg/m ³ (Employee)

2682-20-4 2-Methyl-2H-isothiazol-3-one

Oral	Long term exposure	0.027 mg/kg bw/d (Consumer)
	Short term exposure	0.053 mg/kg bw/d (Consumer)
Inhalative	Local - Long term exposure	0.021 mg/m ³ (Consumer)
		0.021 mg/m ³ (Employee)
	Local - Short term exposure	0.34 mg/m ³ (Consumer)
		0.34 mg/m ³ (Employee)

PNECs
13463-67-7 Titanium dioxide ($\geq 1\%$ particles $\leq 10\mu\text{m}$)

Freshwater	0.127 mg/l
Marine water	1 mg/l
Soil	> 100 mg/kg
Sediments (Freshwater)	> 1,000 mg/kg
Sediments (Marine water)	100 mg/kg
Sewage plant	100 mg/l

2682-20-4 2-Methyl-2H-isothiazol-3-one

Freshwater	0.00339 mg/l (not specified)
Soil	0.047 mg/kg (not specified)
Sediments (Marine water)	0.00339 mg/kg (not specified)
Sewage plant	0.23 mg/l (not specified)

26530-20-1 2-Octyl-2H-isothiazol-3-one

Freshwater	0.0022 mg/l (not specified)
Marine water	0.00022 mg/l (not specified)
Soil	0.0082 mg/kg (not specified)
Sewage plant	0.0475 mg/l (not specified)

Ingredients with biological limit values:

Void

Additional information:

The lists valid during the making were used as basis.

(Contd. on page 7)

EWIPRO EWI-076 PREMIUM BIO SILICONE RENDER

(Contd. of page 6)

8.2 Exposure controls

8.2.1. Information about design of technical facilities

No further data; see item 7.

8.2.2. Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Remove contaminated clothing immediately and thoroughly clean it before using it again. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection. Ensure that washing facilities are available at the work place.

Respiratory protection:



Use suitable respiratory protective device only when aerosol or mist is formed (FFP2 according to EN 149)

Hand protection:



Hand protection: Chemical resistant protective gloves according EN ISO 374

The glove material has to be impermeable and resistant to the product. Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation. Check protective gloves prior to each use for their proper condition. Preventive skin protection by use of skin-protecting agents is recommended. To avoid skin problems reduce the wearing of gloves to the required minimum.

Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Polychloroprene (material thickness ≥ 0.5 mm ; breakthrough time ≥ 480 min.)
Nitrile rubber (material thickness ≥ 0.35 mm ; breakthrough time ≥ 480 min.)
Butyl rubber (material thickness ≥ 0.5 mm ; breakthrough time ≥ 480 min.)
Fluororubber (material thickness ≥ 0.4 mm ; breakthrough time ≥ 480 min.)
Neoprene (material thickness ≥ 0.5 mm ; breakthrough time ≥ 480 min.)

Not suitable are gloves made of the following materials:

Non-liquid-tight gloves made of fabric, leather or similar materials.

Eye/face protection:



In case of splash risk use tightly fitting safety goggles according to EN 166.

(Contd. on page 8)

EWIPRO EWI-076 PREMIUM BIO SILICONE RENDER

(Contd. of page 7)

Body protection:

Protective work clothing

Risk management measures:

An operator training/guidance in the correct use of personal protective equipment is necessary to ensure the required level of effectiveness.

8.2.3. Environmental exposure controls

Avoid release in the environment. Use the surplus or dispose it of properly.

SECTION 9: Physical and chemical properties
9.1 Information on basic physical and chemical properties**General Information**

Physical state	Liquid
Appearance:	
Form:	Pasty
Colour:	Different according to colouring
Odour:	Mild
Odour threshold:	Not safety relevant
pH at 20 °C (68 °F)	8 - 10
Change in condition	
Melting point/freezing point:	~ 0 °C (~ 32 °F) (ISO 3016)
Boiling point or initial boiling point and boiling range	100 °C (212 °F)
Flammability	Product is not flammable.
Flash point:	Not applicable
Auto-ignition temperature:	> 400 °C (> 752 °F) (DIN 51794)
Decomposition temperature:	> 825°C to CaO and CO ₂
Oxidising properties:	None
Explosive properties:	Product does not present an explosion hazard.
Lower and upper explosion limit	
Lower:	Not determined
Upper:	Not determined
Ignition temperature:	Product is not selfigniting.
Vapour pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
Density and/or relative density	
Density at 20 °C (68 °F):	1.4 - 1.6 g/cm ³ (11.68 - 13.35 lbs/gal)
Particle size	
Viscosity:	
Dynamic at 20 °C (68 °F):	> 5,000 mPas (DIN 53019)
Solubility	
Water:	Fully miscible
Partition coefficient n-octanol/water (log value)	Not determined
Solids content:	82 - 86 %
Solvent content:	
Organic solvents:	0.2 %
VOC without water (EC):	0 g/l
VOC with water (EC):	0 g/l

(Contd. on page 9)

EWIPRO EWI-076 PREMIUM BIO SILICONE RENDER

(Contd. of page 8)

VOC with water (EC):	0 %
-----------------------------	-----

9.2 Other information
Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity
10.1 Reactivity

No dangerous reactions known.

10.2 Chemical stability:

The product is stable as long as it is stored properly and dry.

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

No dangerous reactions known.

10.4 Conditions to avoid

No further relevant information available.

10.5 Incompatible materials

No further relevant information available.

10.6 Hazardous decomposition products

No dangerous decomposition products known.

Minimum storage life:

Minimum storage life (+5°C up to 25°C): See indication on package.

Additional information:

No further relevant information available.

GB

(Contd. on page 10)

EWIPRO EWI-076 PREMIUM BIO SILICONE RENDER

(Contd. of page 9)

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

The product was not investigated. The statement is derived from the properties of the single components.

Acute toxicity:

Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

1317-65-3 Limestone (Calcium carbonate)

Oral	LD ₅₀	6,450 mg/kg (Rat) (RTECS Data)
------	------------------	--------------------------------

13463-67-7 Titanium dioxide ($\geq 1\%$ particles $\leq 10\mu\text{m}$)

Oral	LD ₅₀	> 5,000 mg/kg (Rat) (OECD 425)
	Carcinogenicity	(Mouse) (ECHA Registration dossier) no effects observed
Dermal	LD ₅₀	> 5,000 mg/kg (Rabbit)

2682-20-4 2-Methyl-2H-isothiazol-3-one

Oral	LD ₅₀	232 - 249 mg/kg (Rat) (OECD 401)
Dermal	LD ₅₀	242 mg/kg (Rat) (OECD 402)
Inhalative	LC ₅₀ (4h)	0.05 mg/l (ATE)
	LC ₅₀ (4h)	0.11 mg/l (Rat) (OECD 403)

26530-20-1 2-Octyl-2H-isothiazol-3-one

Oral	LD ₅₀	125 mg/kg (ATE)
		125 mg/kg (Rat) (OECD 401)
Dermal	LD ₅₀	311 mg/kg (ATE)
		311 mg/kg (Rat) (OECD 402)
Inhalative	LC ₅₀ (4h)	0.5 mg/l (ATE)

64359-81-5 4,5-dichloro-2-octyl-2H-isothiazol-3-one

Oral	LD ₅₀	567 mg/kg (ATE)
Inhalative	LC ₅₀ (4h)	0.05 mg/l (ATE)
	LC ₅₀ (4h)	0.055 - 0.53 mg/l (Rat)

Other information (about experimental toxicology):

13463-67-7 Titanium dioxide ($\geq 1\%$ particles $\leq 10\mu\text{m}$)

Oral	OECD 414 (Prenatal Developmental Toxicity)	(Rat) no effects observed
Irritation of skin	OECD 404 (skin)	(Rabbit) not corrosive
Irritation of eyes	OECD 405 (eye)	(Rabbit) not irritant
Sensitisation	OECD 429 (LLNA)	(Mouse) not sensitizing
	OECD 421 (Reproduction screening test)	(Rat) no effects observed

2682-20-4 2-Methyl-2H-isothiazol-3-one

Oral	OECD 408 (Repeated dose oral toxicity 90d)	19 mg/kg bw/day (Rat)
------	--	-----------------------

(Contd. on page 11)

EWIPRO EWI-076 PREMIUM BIO SILICONE RENDER

(Contd. of page 10)

Irritation of skin	OECD 404 (skin)	(Rabbit) corrosive
Sensitisation	OECD 406 (sensitization)	(Guinea pig) sensitizing
26530-20-1 2-Octyl-2H-isothiazol-3-one		
Oral	OECD 471 (In vitro - Mutation, Ames-Test)	(Salmonella typhimurium) Negative
Irritation of skin	OECD 404 (skin)	(Rabbit) Corrosive Category 1B
Irritation of eyes	OECD 405 (eye)	(Rabbit) Irreversible effects Category 1
Sensitisation	OECD 406 (sensitization)	(Guinea pig) Sensitizing Category 1

Primary irritant effect:
On the skin:

Based on available data, the classification criteria are not met.

On the eye:

Based on available data, the classification criteria are not met.

Sensitization:

Sensitising effect by skin contact is possible by prolonged exposure.

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

Specific target organ toxicity - single exposure (STOT SE):

Based on available data, the classification criteria are not met.

Specific target organ toxicity - repeated exposure (STOT RE):

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Practical experience

No further relevant information available.

General comments

No further relevant information available.

11.2 Information on other hazards
Endocrine disrupting properties

55406-53-6 3-Iodo-2-propynylbutylcarbamate

List II

SECTION 12: Ecological information
12.1 Toxicity

The product was not investigated. The statement is derived from the properties of the single components.

(Contd. on page 12)

EWIPRO EWI-076 PREMIUM BIO SILICONE RENDER

(Contd. of page 11)

Aquatic toxicity:

1317-65-3 Limestone (Calcium carbonate)

LC ₅₀ (96h)	> 100 mg/l (Fish - oncorhynchus mykiss) (OECD 203)
LC ₅₀ (48h)	> 100 mg/l (Water flea - daphnia magna) (OECD 202)
EC ₅₀	> 14 mg/l (Algae - desmodesmus subspicatus) (OECD 201)
	> 1,000 mg/l (Activated sewage sludge) (OECD 209)

13463-67-7 Titanium dioxide (≥ 1% particles ≤ 10µm)

LC ₅₀ (48h)	5.5 mg/l (Water flea - daphnia magna)
LC ₅₀ (96h Marine water)	> 10,000 mg/l (Fish)
LC ₅₀ (96h Freshwater) (static)	> 100 mg/l (Goldfish) (OECD 203)
EC ₅₀ (48h)	> 1,000 mg/l (Water flea - daphnia magna) (ASTM Standard E729)
EC ₅₀ (72h)	5.83 mg/l (Algae - pseudokirchneriella subcapitata)
EC ₅₀ (3h)	> 1,000 mg/l (Activated sludge organisms) (OECD 209)
EC ₅₀ (7d)	> 100 mg/l (Lemna minor) (OECD 221)
NOEC (48h)	1 mg/l (Water flea - daphnia magna)
NOEC (21d)	> 10 mg/kg (Water flea - daphnia magna) (OECD 202)
NOEC (28d) (static)	> 100 mg/l (Chironomus riparius) (OECD 219)
	Soil
NOEC (32d)	> 1 mg/l (Algae - scenedesmus quadricauda)
NOEC (8d)	> 1,000 mg/l (Fish - danio rerio) (OECD 212)

2682-20-4 2-Methyl-2H-isothiazol-3-one

LC ₅₀ (96h Marine water)	2.98 mg/l (Water flea - daphnia magna)
LC ₅₀ (96h Freshwater)	0.934 mg/l (Water flea - daphnia magna)
LC ₅₀	4.77 mg/l (Fish) (OECD 203)
EC ₁₀	0.044 mg/l (Water flea - daphnia magna) (OECD 211)
	4.93 mg/l (Fish)
EC ₅₀	41 mg/l (Activated sewage sludge) (OECD 209)
	0.103 mg/l (Algae - pseudokirchneriella subcapitata) (OECD 201)
EC ₅₀ (16h)	2.3 mg/l (Pseudomonas putida)

26530-20-1 2-Octyl-2H-isothiazol-3-one

LC ₅₀ (96h)	0.03 mg/l (Fish - oncorhynchus mykiss)
LC ₅₀ (96h Freshwater)	0.122 mg/l (Fish)
EC ₁₀	0.068 mg/l (Algae)
	0.022 mg/l (Fish)
	0.035 mg/l (Aquatic invertebrates)
EC ₅₀	30.4 mg/l (Activated sewage sludge)
EC ₅₀ (48h)	0.32 mg/l (Water flea - daphnia magna)
	0.42 mg/l (Water flea - daphnia) (OECD 202)
EC ₅₀ (72h)	0.084 mg/l (Algae scenedesmus subcapitatus) (OECD 201)
	S 63
EC ₅₀ (96h)	0.047 mg/l (Fish - oncorhynchus mykiss) (OECD 203)
EC ₅₀ /LC ₅₀	0.15 mg/l (Algae)
	0.181 mg/l (Aquatic invertebrates)
IC ₅₀ (72h)	0.084 mg/l (Algae scenedesmus subcapitatus) (OECD 201)

(Contd. on page 13)

EWIPRO EWI-076 PREMIUM BIO SILICONE RENDER

(Contd. of page 12)

64359-81-5 4,5-dichloro-2-octyl-2H-isothiazol-3-one

LC ₅₀ (96h)	0.014 mg/l (Perch - leporinus macrochirus) (OECD 203)
	0.0027 mg/l (Fish - oncorhynchus mykiss)
EC ₅₀	5.7 mg/l (Activated sludge organisms)
ErC ₅₀ (72h)	0.077 mg/l (Algae - pseudokirchneriella subcapitata) (OECD 201)
EC ₅₀ (48h)	0.0057 mg/l (Water flea - daphnia magna)
EC ₅₀ (72h)	0.048 mg/l (Algae - pseudokirchneriella subcapitata) (OECD 201)
NOEC (96h)	0.00056 mg/l (Fish - oncorhynchus mykiss)

12.2 Persistence and degradability

A part of the components is biodegradable.

26530-20-1 2-Octyl-2H-isothiazol-3-one

Oral	OECD 309 Simulation Biodegradation - Surface Water	0.6 - 1.4 d (not specified) S 635
------	--	--------------------------------------

12.3 Bioaccumulative potential

26530-20-1 2-Octyl-2H-isothiazol-3-one

OECD 107 LogKow (Shake Flask Method)	2.92 (n-Octanol / Water)
--------------------------------------	--------------------------

12.4 Mobility in soil

No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT:

This substance/mixture contains no components classified as persistent, bioaccumulative and toxic (PBT) at levels of 0.1% or higher.

vPvB:

This substance/mixture contains no components classified as very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects

Literature

No further relevant information available.

Ecotoxicological effects:

No further relevant information available.

Behaviour in sewage processing plants:

2682-20-4 2-Methyl-2H-isothiazol-3-one

EC ₂₀ (3h)	2.8 mg/l (Activated sludge organisms) (DIN 38412-3 TTC-Test)
-----------------------	--

26530-20-1 2-Octyl-2H-isothiazol-3-one

EC ₂₀ (0,5h)	10.4 mg/l (Activated sewage sludge) (TTC-Test 8901 Macherey Nagel)
EC ₂₀ (3h)	7.3 mg/l (Activated sewage sludge) (OECD 209)
OECD 303 A Activated Sludge Units	> 83 % (Activated sewage sludge) S 313


(Contd. on page 14)

EWIPRO EWI-076 PREMIUM BIO SILICONE RENDER

(Contd. of page 13)

Additional ecological information:
General notes:

Not hazardous for water.

SECTION 13: Disposal considerations
13.1 Waste treatment methods
Recommendation:


Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Risk of environmental pollution. Follow the applicable regulations on waste disposal. Keep unused products and contaminated packaging sealed. Provide containers for waste collection. Hand over for disposal to a specialist company authorised to carry out such activities. Prevent the product from being released into the environment. Do not allow the product to enter the sewage system. Must not be disposed of with municipal waste. Empty containers can be utilised for energy recovery in a waste incineration plant or, if classified accordingly, collected at a landfill site. Perfectly cleaned packaging can be recycled.

The product contains $\geq 0.01\%$ microplastic particles according to Regulation EU 2023/2055. When processed as intended, these particles are immobilised in a solid matrix or are modified in such a way that they no longer fall under the definition of microplastics. Follow the manufacturer's instructions for use and disposal to avoid releasing the product into the environment. Process leftover product and allow it to harden. Recycle or dispose of the cured residues in accordance with the applicable regulations. Collect the water from the cleaning tools and reuse it or dispose of it in the local sewage system. Do not allow cleaning water to enter the environment.

Dispose of contents/container in accordance with local/regional/national/international regulations.

European waste catalogue

08 01 12	Waste paint and varnish other than those mentioned in 08 01 11
15 01 02	Plastic packaging

08 01 12 for residues of the unprocessed product

15 01 02 for the completely emptied packaging

Uncleaned packaging
Recommendation:

Disposal must be made according to official regulations.
Recycle only completely emptied packaging.

Recommended cleansing agents:

Water, if necessary together with cleansing agents.

SECTION 14: Transport information
**14.1 UN number or ID number
ADR, ADN, IMDG, IATA**

Void

(Contd. on page 15)

Safety data sheet according to UK REACH



Printing date 11.11.2025

Version number: RO/ 9 (replaces version 8)

Revision: 19.10.2025

EWIPRO EWI-076 PREMIUM BIO SILICONE RENDER

(Contd. of page 14)

14.2 UN proper shipping name

ADR, ADN, IMDG, IATA	Void
----------------------	------

14.3 Transport hazard class(es)

ADR, ADN, IMDG, IATA Class	Void
----------------------------	------

14.4 Packing group

ADR, IMDG, IATA	Void
-----------------	------

14.5 Environmental hazards

Marine pollutant:	No
-------------------	----

14.6 Special precautions for user	Not applicable
-----------------------------------	----------------

14.7 Maritime transport in bulk according to IMO instruments	Not applicable
--	----------------

UN "Model Regulation":	Void
------------------------	------

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
Poisons Act
Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

7631-99-4	Sodium nitrate	Listed
-----------	----------------	--------

Reportable poisons

1310-73-2	Sodium hydroxide	12% of total caustic alkalinity
-----------	------------------	---------------------------------

Directive 2004/42/EC

IIA(c) 40 - this product contains < 40 g/l VOC (see chapter 9)

Product type: PAINTS AND VARNISHES

- Product subcategory: Exterior walls of mineral substrate
- Water-borne coatings, Limit value: 40 g/l

Directive (EU) 2012/18
Named dangerous substances - ANNEX I :

None of the ingredients is listed.

REGULATION (EC) No 1907/2006 ANNEX XVII :

Conditions of restriction: 78

Additional information on Entry 78

The estimated overall proportion of microplastics in the mixture is approx. 0.099 %

Process the product in closed systems or with suitable extraction/filtering techniques avoid release to soil wastewater surface water. Preferably clean equipment surfaces mechanically after use e.g. cloths collect residues as solid waste. Collect cleaning waters separately and forward them to appropriate disposal do not discharge into the sewer system. Collect product residues and contaminated packaging in closed containers do not rinse dispose of in accordance with legal requirements.

(Contd. on page 16)

EWIPRO EWI-076 PREMIUM BIO SILICONE RENDER

(Contd. of page 15)

Synthetic polymer microparticles

26658-88-8	Polyacrylonitrile, Co-Polymer with < 6% Methylacrylate	0.099%
------------	--	--------

Regulation (EU) No 649/2012

Annex I - RESTRICTED EXPLOSIVES PRECURSORS

(Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients are included.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

National regulations:

Waterhazard class:

Generally not hazardous for water

Other regulations, limitations and prohibitive regulations:

· Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (UK REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

· Commission Regulation (EU) No 878/2020 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (UK REACH)

· Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

· Regulation (EC) No 1013/2006 of the European Parliament and of the Council of 14 June 2006 on shipments of waste

· Regulation (EC) No 528/2012 of the European Parliament and of the Council of 22 May 2012 concerning the making available on the market and use of biocidal products

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Reasons for changes:

* Data compared to the previous version altered.

Relevant phrases:

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H400 Very toxic to aquatic life.

(Contd. on page 17)

EWIPRO EWI-076 PREMIUM BIO SILICONE RENDER

(Contd. of page 16)

H410 Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

Advice for instructions:

Additional trainings, which go beyond the prescribed training in activities involving hazardous substances are not required.

Department issuing MSDS:

Product safety department (+43/(0)5522-41646-0 / klaus.ritter@fixit-gruppe.com)

Contact:

Dr. Klaus Ritter

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

MAK: Maximale Arbeitsplatz-Konzentration (maximum concentration of a chemical substance in the workplace, Austria/Germany)

PBT: persistent, bioaccumulative and toxic properties

vPvB: very persistent, bioaccumulative properties

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1: Skin corrosion/irritation – Category 1

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Further information:

The information in this safety data sheet describe the safety requirements of our product and is based on our current state of our knowledge. They provide no assurance of product quality. Existing laws, ordinances and regulations, including those that are not mentioned in this data sheet must be observed by the recipient of our products in their own responsibility.