EWIPRO Render Systems

PRO CLEAN

RENDER REMOVER

PRODUCT DATA SHEET

Render Remover is a ready-to-use cleaning solution designed to help remove unwanted render, basecoat and cementitious residues from suitable surfaces.

It can be used on both fresh and dried material and is suitable for removing residues from surfaces such as glass, plastic, stainless steel, ceramic, concrete, metal, vinyl, rubber and other compatible backgrounds.



Intended Uses

Render Remover is intended for removing unwanted silicone render, monocouche render, basecoats and other compatible cementitious residues from suitable surfaces.

It is suitable for professional, industrial and domestic cleaning applications and may be used on stainless steel, plastic, wood, ceramic, glass, rubber, concrete, metal, vinyl and other compatible surfaces.

Technical Specification

Appearance / Physical State	Slightly viscous, clear to slightly opaque liquid
Quantity Per Unit	1L or 5L jerrycan
Consumption	No fixed consumption rate – apply sufficient product to fully cover the affected area and keep it wet throughout the activation period
Relative Density	1.0–1.01 at +20°C
Solubility	Dispersible

Application Temperature	+5°C to +25°C
Activation Time – General Cleaning	Approx. 1 minute
Activation Time – Heavy Residues	Up to approx. 20 minutes
Freezing Point	Approx. -2°C
Boiling Point	Approx. 100°C

Please note: Product consumption and activation time will vary depending on the type, thickness and age of the residue, surface condition and site conditions.

Please see the reverse of this page for directions for use.

Directions for use

Substrate Preparation

Remove loose debris and excess material from the affected area before application.

Before treating delicate, coated or unfamiliar surfaces, test the product on a small inconspicuous area to confirm compatibility.

Product Preparation

Render Remover is supplied ready to use and does not require dilution.

Do not mix with water or other cleaning products.

Application

Apply Render Remover evenly over the affected area using a suitable spray, brush, cloth or other compatible cleaning method.

For general cleaning, allow the product to work for approximately 1 minute before agitating and removing the residue.

For heavier, dried or stubborn render and basecoat residues, allow the product to remain on the surface for up to 20 minutes. Keep the treated area wet throughout the activation period by applying additional product where necessary.

Agitate using a suitable cloth, brush or cleaning implement and remove the loosened material. Repeat the process where required until the residue has been removed.

Application Conditions

Apply when the air, substrate and product temperatures are between +5°C and +25°C.

Protect from frost and direct sunlight during storage and use.

Clean-up

Remove loosened residue using a suitable cloth, brush or cleaning implement. Clean application equipment appropriately after use.

Packaging & Storage

Render Remover is supplied in 1L and 5L jerrycans.

Store unopened in the original packaging in a cool, dry place. Protect from frost and direct sunlight.

Shelf life is up to 12 months from the date of manufacture when stored correctly.

Compliance with Standards

N/A

Safety Measures

Avoid contact with the eyes. In the event of eye contact, rinse immediately with plenty of clean water and seek medical attention where necessary.

Do not ingest and keep out of reach of children. Contact with the product may cause irritation. Refer to the latest Safety Data Sheet for full handling, first aid and protective equipment guidance.

General Information

This data sheet replaces all previous editions. The information provided is based on current knowledge and practical experience, and while it has been compiled with care, it is not guaranteed to be accurate, complete or suitable for all applications. It is the responsibility of the user to verify the product's suitability for their specific use case. No legal obligations are established by this document.

Data Sheet Revision Date: 30/10/2026

Address:
Unit 1-2 King George's Trading Estate,
Davis Road,
Chessington,
England,
KT9 1TT

Email:
info@ewipro.com

Phone:
0800 133 7072