


QuietAir QT100

Toilet, bathroom and en-suite ventilation



KEY FEATURES

- Two speed ventilation up to 25 l/s (90 m³/h)
- Awarded Quiet Mark by Noise Abatement Society
- Power consumption from only 5 W
- Interval timer for routine auto extraction
- Long-life ball bearings with approx. 40,000 hr life
- Suitable for installation anywhere in Zone 1 of bathrooms when installed with an RCD
- 3 year warranty



Designed and engineered in Germany, the QuietAir range features high-efficiency, low-energy, and ultra-quiet performance. With a variety of controls and features, there is a perfect solution for every application. The simple and compact design will fit perfectly with your decor.

This elegant, discreet axial fan range includes various control options that activate the fan only when needed - remote switching, timer, humidity timer, and motion sensor with timer. By using exceptionally low energy, it helps reduce carbon emissions and save on energy bills.

Room refresh (interval timer) enables automatic extraction at pre-set times if required.

MODELS


Basic	Control by remote switch
Timer	Features a 6-21 minute overrun and automatic room refresh at 8, 12 or 24 hour intervals
Humidity Timer	Adjustable Humidity 60 to 90% RH with adjustable timer
Motion Sensor Timer	Motion sensor activation



TECHNICAL DATA


Specification	QuietAir QT100B	QuietAir QT100T	QuietAir QT100HT	QuietAir QT100MST
Air flow m ³ /h*	75 / 90			
Air flow l/s*	21 / 25			
Fan type	Axial			
Controls	Basic	Timer	Humidity Timer	Motion Sensor Timer
Mounting	Wall / Ceiling			
Sound pressure dB(A)@3m	25 / 30			
Delay start (min)	No	0, 45, 90, 120 sec's	2	No
Adjustable timer (min)	No	6, 10, 15, 21	6, 10, 15, 21	15
Adjustable humidity (%RH)	-	-	60 - 90	-
Interval timer, auto start (hrs)	-	0, 8, 12, 24	-	-
Power Watts	5 / 9			
Amps	0.04 / 0.06			
Specific Fan Power (SFP)	0.24			
Building Regulations ADF	Yes			
Duct Diameter (mm)	100			
Voltage	230 V / 1 ph / 50 Hz			
Rating	IP45			
Max ambient temperature	40°C			
Weight (kg)	0.8			
Dimensions (H x W x D) mm	147 x 147 x 131			
Part No.	9041259	9041260	9041261	9041262
EAN Barcode	5019009306445	5019009306452	5019009306469	5019009306476

DIMENSIONS




Model	A	B	C	D	E
QuietAir QT100	147	35	96	98	52

PERFORMANCE



CONTROLS & ACCESSORIES

 <p>Cavity Wall Kit - White No: 90001018 Ø100mm x 350mm Rigid Duct and Square Grill in White with Fixing Kit</p>	 <p>Cavity Wall Kit - Terracotta No: 90001015 Ø100mm x 350mm Rigid Duct and Square Grill in Terracotta with Fixing Kit</p>	 <p>High Rise Cavity Wall Kit No: 9021451 Ø100mm x 400mm Rigid Duct and Round Grille in Brown</p>	 <p>Flexible Duct Kit - White No: 72643602 Ø100mm x 3000mm Flexible Duct and Square Grill in White with Fixing Kit</p>
--	--	---	--

Others products available from airflow.com

Call: 01494 525252

Visit: airflow.com




Airflow Developments Limited
Aidelle House, Lancaster Road,
Cressex Business Park,
High Wycombe, Buckinghamshire,
United Kingdom, HP12 3QP

E-mail: info@airflow.com
Telephone: +44 (0) 1494 525252

airflow.com

© Airflow Developments Limited. Airflow Developments Limited reserve the right, in the interests of continuous development, to alter specifications without prior notice. All orders are accepted subject to our conditions of sale which are available on request



80001414 - Issue 5 09/25